



PIC-VPM02MAZ148

2MP/60FPS, Low light, motorized lens 33x, Autofocus



Sensor & Lens	
Type	CMOS, 2MP, 1/2.8"
Min illumination	Color: 0.001 Lux B/W: 0 Lux with IR
Day& Night	IR Cut Filter with Auto Switch
WDR	120 db
DNR	2D, 3D
Electronic shutter	1s to 1/100,000s
Lens	Motorized 4.5-148mm, 33x Auto and Manual Iris
Viewing angle (H)	56.2° - 2.6°
Pan/Tilt	
Pan range/Speed	360° endless/0.1°/s ~ 200°/s, Preset speed: 300°/s
Tilt range/Speed	-15° ~ 90° auto flip/0.1° ~ 200°/s, Preset speed: 240°/s
Options	Preset, Patrol, Auto Tracking
Encoding standard	
Video compression	H.265+, H.265, H.264, MJPEG
Video Bit rate	128Kbps-16Mbps, CBR/VBR
No. Streams	3 - 1920x1080, 1920x1080, 720x576
Audio compression	G.711A/G.711U
Image Index	
Max Image size	1920x1080
VCA	Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios, Auto Tracking
Frame Rate	60fps@2MP (1920x1080)
Image setup	Brightness, Saturation, Contrast, ROI, Flip Mode, HLC, BLC, Defog, Privacy Mask, Picture Overlay
Network function	
Intelligent Alarm	Motion Detection, IP Conflict, ARP protection, Mask Alarm, Tampering Alarm, Alarm in/Out, user authentication
Protocols	L2TP, IPV4, IGMP, ICMP, ARP, HTTP, 802.1x, FTP, SMTP, UPnP, SIP, DNS, DDNS, NTP, RTP, RTSP, TCP, RTCP, SNMP, UDP, DHCP, PPPoE, QoS
Interface protocol	ONVIF (Profile S, G, T), API, SDK
General function	Reset Button
Function Interface	
Network port	1x RJ45 10M / 100M
Local storage	MicroSD Card Slot, up to 256GB
Video port	1 x BNC
Audio (in/out)	1/1, Two-way audio
Serial interface	1x RS485
Alarm interface (in/out)	2/1
General Specification	
MTBF	50,000 hours
Surge Protection	TVS 6000V
Approval	CE, FCC, UL
IR type	Smart IR LEDs, laser beam balanced with the camera optical zoom
IR distance	500m
Operation conditions	-40°C~65°C, 0~95% RHG
Power supply	C 24V ±25%, DC 24V±25%, PoE (PSE Required)
Power consumption	Max. 47W
Protection rate	IP66
Mounting	Surface mount
Dimensions (mm)	385x227x227
Weight (Kg)	5.6 KG (Camera Only)

مشخصات مهم

- دوربین دام موتوری ۲ مگاپیکسل
- ۶۰ عکس در ثانیه
- لولایت
- بزرگنمایی ۳۳ برابر
- روز / شب
- محدوده داینامیکی 120db
- کاهش نویز دو بعدی و سه بعدی
- آنالیز هوشمند تصاویر
- نوردهنده مادون قرمز
- ردیاب لیزری هوشمند
- دارای سه استریم مستقل
- مقاوم در برابر شرایط محیطی
- مقاوم در برابر ولتاژهای سرگردان تا 6KV
- مصرف انرژی پائین