



PIC-VX02SA

2MP/60FPS, Super starlight, LightHunter



Sensor	
Type	CMOS, 2mp 1/2.8"
Min illumination	Color: 0.0005 Lux, B/W: 0.0001 Lux
Day& Night	IR Cut Filter with Auto Switch
WDR	120 db
DNR	2D, 3D DNR
Electronic shutter	1s to 1/100,000s
Lens mount	CS
Iris	DC-Iris/P-Iris, DC 5V (4 Pins)
Encoding standard	
Video compression	H.265+, H.265, H.264, MJPEG
Video Bit rate	128Kbps-16Mbps
No. Streams	3 – 1920x1080, 1280x720, 720x576
Audio compression	G.711A, G.711U
Image Index	
Max Image size	1920x1080
VCA	Smart intrusion prevention, support false alarm filtering, include Cross Line, Intrusion, Enter Area, Leave Area detection People Counting, support people flow counting and crowd density monitoring, suitable for different statistical scenarios
Frame Rate	60 fps @ 2MP (1920x1080)
Image setup	Brightness, Saturation, Contrast, Flip Mode, HLC, Defog, Privacy Mask, Picture Overlay
Network function	
Intelligent Alarm	Motion Detection, IP Conflict, MAC Conflict, Mask Alarm
Protocols	IPv4, TCP, ICP, ARP, UDP, PPPoE, RTP, HTTP, HTTPS, FTP, SMTP, UPnP, SNMP, DHCP, DNS, DDNS, NTP, FTP, RTSP, RTCP, QoS
Interface protocol	ONVIF (Profile S, G, T), SDK, CGI
General function	Reset Button
Function Interface	
Network port	1x RJ45 10M / 100M
Local storage	Micro SD, up to 256GB
Video port	YES
Audio (in/out)	1/1
Serial interface	Yes, RS485
Alarm interface (in/out)	2/1
General Specification	
MTBF	50,000 hours
Surge Protection	TVS 6000V
Approval	CE, CB, FCC, UL
Operation conditions	-20°C~50°C, 0~95% RHG
Power supply	DC 12 V ± 25%, AC 24 V ± 25%, POE (IEEE 802.3af)
Power consumption	Max. 7W
Dimensions (mm)	152.5x71x65
Weight (Kg)	0.38 KG (Camera Only)

مشخصات مهم

- دوربین باکس ۲ مگاپیکسل
- ۶۰ عکس در ثانیه
- سوپر استارلایت
- روز / شب
- محدوده داینامیکی 120db
- کاهش نویز دو بعدی و سه بعدی
- آنالیز هوشمند تصاویر
- دارای سه استریم مستقل
- پشتیبانی از کارت حافظه داخلی
- مقاوم در برابر ولتاژهای سرگردان تا 6KV
- مصرف انرژی پائین