



PIR-V6416R

NVR 64 CH, Raid control, up to 160TB, ANR,



مشخصات مهم

Recording	
Input channels	64
Max recording Res.	12MP
Playback Res. @ FPS	3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080p@30
Recording mode	Schedule, Permanent, Event, Motion, Alarm, VCA
Supported cameras	PAVAN, Axis, Bosch, Dallmeier, Dahua, Exom, Hikvision, inMotion, Nazer, Tiandy, UNV & all ONVIF cameras
Decoding	
Video compression	H265+, H.265, H.264
Input bandwidth (Mbps)	384
Output bandwidth(Mbps)	384
Live Res. @ FPS	4 x 12MP@20, 4 x 4K@30, 16 x 1080P@30,
Display splits	1, 4, 6, 8, 9, 16, 25, 36, 64
Smart function	
Password policy	3 level
VCA	N/A
Smart Backfill	Yes (ANR)
Mobil monitoring	Yes (Android, iOS)
Alarm management	Anti-disassembly alarm, Network disconnected, Disk offline, Disk abnormal, Illegal access, Running out of space, Space used up, Array damaged, Array degraded, Recording/ Snapshot abnormal, Motion Detection, IP Conflict, MAC Conflict, Mask Alarm
Interfaces	
Storage option	16x SATA, Max 10 TB for each and 1x eSATA, 2 miniSAS
Raid control	RAID 0, 1, 5, 6, 10, 50, 60
Video	HDMI:1 1080, HDMI2 4K, 1x VGA 1080, 2x optional slots (4-ch HDMI or 6-ch HDMI outputs per card
Audio In/ Out	1/1
Ethernet	4x RJ45 10M/100M/1000M, 2x 1000M SFP Ethernet
PoE	N/A
USB	Rear 4x USB3.0
Serial (PTZ control)	RS-232, RS-485
Contact In/ Relay out	24/8
Backup	USB, LAN
Network protocol	
Protocols	IPV4, IPV6, TCP, UDP, HTTP, HTTPS, UPnP, DHCP, DDNS, NTP, FTP, Unicast, Multicast, RTSP, SNMP
Interface protocol	ONVIF (Profile S, G, C, Q, A, T), P2P, SDK
Search function	
Search mode	Date, time, event
Intelligent search	N/A
Playback	16 CH Synchronous
Back up format	Native format (TS), MP4
Log book	Yes, via system, warning Alarm, user, operation
General Specification	
MTBF	50,000 hours
Approval	CE, FCC, UL
Operation conditions	-10 °C ~ +55 °C, 10 % ~ 90 %
Power supply	100-240 VAC, Redundant power supply optional
Power consumption	50W (Without HDD)
Mounting	3unit, Rackmount
Dimensions (mm)	482x477x131
Weight (Kg)	10KG

- رکوردر ۶۴ کاناله
- ضبط انواع دوربین ها تا ۱۲ مگاپیکسل
- پشتیبانی از فشرده سازی H. 265+
- پشتیبانی از قابلیت Raid
- پشتیبانی از کارت حافظه دوربین
- انتقال تصویر روی موبایل
- مدیریت هشدارها
- مصرف انرژی حداقل
- نصب داخل رک