



## PSW-D0802SPI

10 Port, Layer2 manageable, PoE Switch



Interface	
Total port	10
RJ45 PoE port	8x 10/100/1000 Mbps
RJ45 Uplink port	N/A
SFP Uplink port	2x 10/100/1000 Mbps
PoE budget	240W
Network performance	
Protocols	SNMP, DTP, PAgP, LACP, UDLD, DHCP, ARP, IGMP, CSMA/CD, VTP, TFTP, NTP, SSH, RTSP, MSTP, STP, BOOTP, VLAN,
Standard	IEEE802.3x, IEEE802.3u, IEEE802.3az, IEEE802.3af, IEEE802.3at
Transfer rate	10Mbps @half duplex , 20Mbps@full duplex, 10BASE-T: 15Kbps/port 100Mbps@half duplex, 200Mbps@full duplex,100BASE-TX: 158Kbps/port 1000Mbps@half duplex, 2000Mbps@full duplex, 1000BASE-TX: 1.5Mbps/port
PoE cable length	10/100Base-TX: Cat5e or above (100m) 1000Base-TX: Cat6 or higher UTP(120m)
Internal bandwidth	20 Gb
MAC Address table	64Kb
Console	Web & RS232, Telnet
Transfer pattern	Store & Forward
Manageable	Yes
Port management	Yes
General Specification	
Developed for	IT, Security, VoIP
MTBF	100,000 hrs. MIL-HDBK-217F (25°)
Approval	EN55016
Surge protections	Hardware Optional
Fan	No, natural cooling
Operation conditions	-20°C~60°C, 10~90% RH
Power supply	90~220 VAC
Redundant PSU	N/A
Power consumption	Max. 240W with full PoE use
Protection rate	IP51
LED panel	Power, PoE Activity, Data Activity
Case material	Metal
Mounting	Railmount
Dimensions (mm)	155x145x54
Weight (Kg)	1.1Kg

### مشخصات مهم

- سوئیچ ۸ پورت با قابلیت PoE
- لایه ۲ (قابل مدیریت)
- پورت های گیگا بیته
- آپ لینک گیگا بیته فیبرنوری
- ۲۴۰ وات مجموع توان تغذیه
- هماهنگ با پروتکل های سیسکو
- مناسب برای انواع کاربردها
- مدیریت هشدارها
- بدنه فلزی
- نصب داخل تابلو