



## PSW-D2407SPG

31 Port, PoE Switch



Interface	
Total port	31
RJ45 PoE port	24x 10/100 Mbps
RJ45 Uplink port	1x 10/100 Mbps
RJ45 Uplink port	3x 10/100/1000 Mbps
SFP Uplink port	3x 10/100/1000 Mbps
PoE budget	400W
Network performance	
Protocols	SNMP, DTP, PAgP, LACP, UDLD, DHCP, ARP, IGMP, CSMA/CD, VTP, TFTP, NTP, SSH, RTSP, MSTP, STP, BOOTP, VLAN,
Standard	IEEE802.3x, IEEE802.3u, IEEE802.3az, IEEE802.3af, IEEE802.3at
Transfer rate	10Mbps @half duplex , 20Mbps@full duplex, 10BASE-T: 15Kbps/port 100Mbps@half duplex, 200Mbps@full duplex,100BASE-TX: 148Kbps/port 1000Mbps@half duplex, 2000Mbps@full duplex, 1000BASE-TX: 148Kbps/port
PoE cable length	10/100Base-TX: Cat5e or above (100m) 1000Base-TX: Cat6 or higher UTP(150m)
Internal bandwidth	15 Gb
MAC Address table	1 Mb
Console	N/A
Transfer pattern	Store & Forward
Manageable	N/A
Port management	Yes
General Specification	
Developed for	IT, Security, VoIP
MTBF	100,000 hrs. MIL-HDBK-217F (25°)
Approval	EN55016
Surge protections	Hardware Optional
Fan	No, natural cooling
Operation conditions	-15°C~50°C, 10~90% RH
Power supply	110~240 VAC
Redundant PSU	N/A
Power consumption	Max. 400W with full PoE use
Protection rate	IP51
LED panel	Power, PoE Activity, Data Activity
Case material	Metal
Mounting	Rackmount
Dimensions (mm)	440x273x45
Weight (Kg)	3 Kg

### مشخصات مهم

- سوئیچ ۲۴ پورت با قابلیت PoE
- پورت های مگا بایتی
- آپ لینک گیگا بایتی فیبر
- آپ لینک گیگا بایتی مسی
- ۴۰۰ وات مجموع توان تغذیه
- مناسب برای انواع کاربردها
- مدیریت هشدارها
- بدنه فلزی
- نصب داخل رک