



PIR-V3204

NVR 32 CH, up to 40 TB, VCA, ANR



| Recording | |
|------------------------|--|
| Input channels | 32 |
| Max recording Res. | 12MP |
| Playback Res. @ FPS | 3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080p@30 |
| Recording mode | Schedule, Permanent, Event, Motion, Alarm, VCA |
| Supported cameras | PAVAN, Axis, Bosch, Dallmeier, Dahua, Exom, Hikvision, inMotion, Nazer, Tiandy, UNV & all ONVIF cameras |
| Decoding | |
| Video compression | H265+, H.265, H.264 |
| Input bandwidth (Mbps) | 320 |
| Output bandwidth(Mbps) | 320 |
| Live Res. @ FPS | 3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080p@30, 32x 960p@25 |
| Display splits | 3, 4, 5, 7, 9, 10, 12, 16, 32 |
| Smart function | |
| Password policy | 3 level |
| VCA | Intrusion Detection, Cross Line Detection, Audio Detection People Counting, Defocus Detection, Scene Change Detection, Auto Tracking, Object Left Behind, Object Removed |
| Smart Backfill | Yes (ANR) |
| Mobil monitoring | Yes (Android, iOS) |
| Alarm management | Anti-disassembly alarm, Network disconnected, Disk offline, Disk abnormal, Illegal access, Running out of space, Space used up, Array damaged, Array degraded, Recording/ Snapshot abnormal, Motion Detection, IP Conflict, MAC Conflict, Mask Alarm |
| Interfaces | |
| Storage option | 4x SATA, Max 10 TB for each |
| Raid control | N/A |
| Video | HDMI1 1080, HDMI2 4K, 1x VGA 1080 |
| Audio In/ Out | 1/1 |
| Ethernet | 2x RJ45 10M/100M/1000M |
| PoE | N/A |
| USB | Front: 2x USB 2.0/ Rear 1x USB3.0 |
| Serial (PTZ control) | RS-485 |
| Contact In/ Relay out | 16/4 |
| Backup | USB, LAN |
| Network protocol | |
| Protocols | IPV4, IPV6, TCP, UDP, HTTP, HTTPS, UPnP, DHCP, DDNS, NTP, FTP, Unicast, Multicast, RTSP, SNMP |
| Interface protocol | ONVIF (Profile S, G, T) ,P2P,SDK |
| Search function | |
| Search mode | Date, time, event |
| Intelligent search | VCA |
| Playback | 16 CH Synchronous |
| Back up format | Native format (TS), MP4 |
| Log book | Yes via system, warning Alarm, user, operation |
| General Specification | |
| MTBF | 50,000 hour |
| Approval | CE, FCC, UL |
| Operation conditions | -10 °C ~ +55 °C, 10 % ~ 90 % |
| Power supply | 12 VDC |
| Power consumption | 12W (Without HDD) |
| Mounting | 1unit, Rackmount |
| Dimensions (mm) | 440x344x50 |
| Weight (Kg) | 3.2KG |

مشخصات مهم

- رکوردر ۳۲ کاناله
- ضبط انواع دوربین ها تا ۱۲ مگاپیکسل
- پشتیبانی از فشرده سازی H. 265+
- آنالیز هوشمند تصاویر
- پشتیبانی از کارت حافظه دوربین
- انتقال تصویر روی موبایل
- مدیریت هشدارها
- مصرف انرژی حداقل
- نصب داخل رک